



Accel XL 8 SAE 20W-50



HIGH PERFORMANCE MULTIGRADE PASSENGER VEHICLE ENGINE OIL

SPECIFICATIONS

API SG/CF

DESCRIPTION

Accel XL8 is high performance engine oil for all vehicles, formulated with a proprietary mixture of refined base oils and a superior additive system that provides an excellent protection and engine cleanliness. Accel XL8 reduces engine's wear and protects it from the rust and deposit build-up (soot, varnish, lacquer...).

ADVANTAGES

- Optimal protection engine's wear.
- Facilitates start when cold.
- Guarantees an excellent engine protection in high temperature.
- Reduces oil consumption.

APPLICATIONS

Accel XL8 can be used in a variety of gasoline and diesel engines requiring a level performance API SG/CF.



TYPICAL PROPERTIES

	Test Method	Accel XL8
Grade SAE		20W-50
Viscosity @ 40°C - cSt	ASTM D 445	149
Viscosity @ 100°C - cSt	ASTM D 445	17
Viscosity index	ASTM D 2270	123
TBN - mg KOH/g	ASTM D 2896	8.7
Pour Point°C	ASTM D 97	-27
Flash Point°C	ASTM D 92	230
Density @ 20°C - kg/l	ASTM D 4052	0,896

The characteristic values appeared on the top in the table are typical values given only as an indication.

HEALTH AND SAFETY

This product used as our recommendation for intended application not expected to produce any particular risk. A safety data sheet of this product is available for a simple request from your sales contact office or via internet. In case of used oil elimination, please respect the regulation and protect the environment.