



Accel XL10 SAE 20W-50



HIGH PERFORMANCE MULTIGRADE ENGINE OIL

SPECIFICATIONS

API SL/CF

DESCRIPTION

Accel XL10 is premium mineral multigrade oil that exceeds the last standards required in all modern engines. It is formulated with a propriety mixture of high refine base oil with additive technology that provides an excellent engine protection and cleanness.

FEATURES AND BENEFITS

Accel XL10 reduces engine wear and protects it against rust and deposits build-up (soot, varnish, lacquer...).

APPLICATIONS

Accel XL10 is recommended for gasoline and diesel modern engines requiring a level performance API SL/CF .

TYPICAL PROPRIETIES

	Test Method	Accel XL 10
Grade SAE		20W-50
Viscosity @ 40°C - cSt	ASTM D 445	140
Viscosity @ 100°C - cSt	ASTM D 445	17
Viscosity index	ASTM D 2270	132
TBN - mg KOH/g	ASTM D 2896	8.4
Pour Point °C	ASTM D 97	-33
Flash Point °C	ASTM D 92	236
Density @ 15°C - kg/l	ASTM D 4052	0.881

The characteristic values appeared on the top in the table are typical values given only as an indication.



Accel XLIO SAE 20W-50



HEALTH AND SAFETY

This product used as our recommendation for intended application not expected to produce any particular risk. A safety data sheet of this product is available for a simple request from your sales contact office or via internet. In case of used oil elimination, please respect the regulation and protect the environment.