



AUTOMATIC TRANSMISSION FLUID

SPECIFICATIONS

GM Dexron II D

DESCRIPTION

ATF II D is a high performance fluid for automatic transmissions vehicles specifying Dexron II D. It is also used as a hydraulic fluid in unique applications.

FEATURES AND BENEFITS

Ola ATF II D is formulated from high-quality conventional base oils combined with a special additive system including viscosity index improvers, antioxidants, and defoamers providing outstanding performance:

- Good thermal and oxidation stability.
- Good anti-wear properties.
- Meets the wear requirement to promote longer transmission life.
- Excellent low-temperature fluidity.
- Effective foam control properties.
- Compatible with all common seal materials used in Type IID transmissions.

APPLICATIONS

Ola ATF II D is recommended for some automatic and manual transmissions in passenger cars and light trucks specifying Dexron IID level performance as well as the related power steering systems.

Ola ATF II D is also suitable for Off-highway transmissions power steering and other hydraulic systems requiring a Dexron II D or Allison C-4 fluid and Industrial hydraulic systems.



TYPICAL PROPERTIES

	Test Method	ATF II D
Viscosity @ 40°C – cSt	ASTM D 445	37
Viscosity @ 100°C – cSt	ASTM D 445	7
Viscosity Index	ASTM D 2270	153
Pour Point °C	ASTM D 97	-44
Flash Point °C	ASTM D 92	200
Density @ 15°C - kg/l	ASTM D 4052	0.870

The characteristic values appeared on the top in the table are typical values given only as an indication.

HEALTH AND SAFETY

This product used as our recommendation for intended application not expected to produce any particular risk. A safety data sheet of this product is available for a simple request from your sales contact office or via internet. In case of used oil elimination, please respect the regulation and protect the environment.