



Accel FUSION 5W-40



HIGH PERFORMANCE SYNTHETIC ENGINE OIL

SPECIFICATIONS

Accel FUSION 5W-40 performances meet the most recent ACEA and API specifications as well the following European OEMs:

- API SN/CF
- ACEA C3
- MB 229.51/226.5
- VW 502.00/505.01
- BMW LL-04
- Porsche A40
- Ford WSS-M2C917A
- RN 0700/0710
- OPEL Dexos 2

DESCRIPTION

Accel FUSION 5W-40 is synthetic engine oil for passenger and light duty diesel cars formulated with modern technology components and synthetic base oils offering excellent qualities.

FEATURES AND BENEFITS

Accel FUSION 5W-40 is specially formulated with the highest quality synthetic base oils and leading additive technology to provide the highest protection in a wide range of operating conditions.



Accel FUSION 5W-40



Key features and benefits include:

- Excellent thermal and oxidation stability to reduce engine deposits and sludge build up to keep engines running reliably.
- Effective detergency/dispersancy : Cleaner engines and long engine life.
- Enhanced frictional properties to help save fuel.
- Excellent low temperature capabilities for reliable cold weather starting allowing fast engine protection.
- High temperature fortified formulation provides reserve protection for the toughest driving conditions.

APPLICATIONS

- Accel FUSION 5W-40 is specifically recommended for use in all types of vehicles, especially modern gasoline or diesel engines (also multi-valve fuel injection engines), turbochargers and other high performance engines.
- Accel FUSION 5W-40 is an excellent choice who is seeking outstanding lubricant. It is intended for all automobiles, light trucks and vans.

TYPICAL PROPERTIES

Characteristics	Methods	Units	Values
Density at 15°C	ASTM D 4052	-	0,849
Kinematic viscosity @ 100°C	ASTM D 445	Cst	14.1
Kinematic viscosity @ 40°C	ASTM D 445	Cst	86,2
Viscosity index	ASTM D 2270	-	169
Flash point (COC)	ASTM D 92	°C	>220
Pour point	ASTM D 97	°C	<-36
TBN	ASTM D 2896	mg KOH/g	7,4
Sulfated ash	ASTM D 874	wt%	0,79

The characteristic values appeared on the top in the table are typical values given only as an indication.



Accel FUSION 5W-40



HEALTH AND SAFETY

This product used as our recommendation for intended application not expected to produce any particular risk. A safety data sheet of this product is available for a simple request from your sales contact office or via internet. In case of used oil elimination, please respect the regulation and protect the environment.